

PYLE[®]
PyleUSA.com

Questions? Comments?

We are here to help!

Phone: (1) 718-535-1800

Email: support@pyleusa.com

California Prop 65 Warning

⚠️ WARNING:

This product contains Nickel carbonate which is known to the state of California to cause cancer birth defects and other reproductive harm. Do not ingest.

For more info go to: www.P65warnings.ca.gov

PYLE[®]
PyleUSA.com



PCS1025B

Wooden Professional Compact Line Array Column Speaker

with 10-Inch Subwoofer, 2 x4-Inch Satellite,

DSP, Wireless BT Streaming, USB, SD, 2.1 Channel, 1880W

USER GUIDE

PLEASE READ THIS MANUAL CAREFULLY BEFORE OPERATION

Features:

- Loudspeaker PA System One
- Rugged, Durable & Reliable Sound
- Wireless BT Streaming Ability
- Wireless BT Music Streaming Ability
- Speaker System: 1x10" Subwoofer, 2x4" Full Arrange Driver
- Built-in Digital Audio Amplifier
- 4 Band DSP Presets to fit your requirements: Flat, Live, Dj, Speech
- 2 x XLR/F ¼" -inch Combo (MIC/Line Input)
- RCA (R+L) Input, XLR (R+L) Output, SpeakOn (R+L) Sat Out
- Connect & Stream Audio from External Devices
- USB Flash Drive & SD Memory Card Readers
- Digital LCD Display
- Rear Panel Rotary Dial & Button Control Center
- SUB Volume, L/R Volume
- Integrated Carry Handles

Wireless BT Streaming:

- Instantly Stream Music from Your BT Devices
- Works with All Your Favorite BT Devices
(iPhone, Android, Smartphone, iPad, Tablet, PC, etc.)
- Wireless BT Version: 5.0
- Wireless BT Range: 100'+ Feet
- Wireless BT Network Name: '**Pyle**'

What's in the Box:

- Wooden Column Speaker System
- Remote Control
- Power Cable
- (2) SpeakOn Cable

Subwoofer Specs:

- Size: 10" -inch
- Impedence: 4 Ohm
- Magnet: 50 oz.
- Voice Coil: 60.6mm, 2.5" -inch
- Sensitivity: 93dB
- Frequency Response: 45Hz - 200Hz

Driver Specs:

- Speaker: 4" -inch
- Impedence: 16 Ohm
- Sensitivity: 90dB
- Voice Coil: Kapton
- Frequency Response: 200Hz-20kHz

Technical Specs:

- Max Power Output: 1880 Watt
- RMS Power Output: 470 Watt
- Amplifier Class: D
- Digital Audio File Compatibility: MP3, WMA
- Maximum SD/USB Flash Memory Support: 32GB
- T.H.D.: 1%
- Crossover Frequency: 200Hz
- Voltage: 100-120V AC 60HZ
- Active Subwoofer Dimensions (L x W x H): 12.6" x 18.1" x 16.93" -inches
- Passive Line Array Dimensions (L x W x H): 5.91" x 6.7" x 6.3" -inches

Function Description

1. LCD screen
2. MP3 control
 - M:** USB/SD/BT/convertor
 - ▶/⏸: Play/Pause
 - FD:** FOLDER
 - ↺: Repeat one / Repeat all / Random
 - ⏮: Previous song
 - ⏭: Next song
3. SD card input
4. USB input
5. Model Sheft of LP extend/ Through/Bass indicator indicated by three different LED light
6. **Phase Indicator:** When light is off, it indicates that the phase is through
7. DSP MODE
8. Subwoofer Limit LED indicator
9. Left Limit LED indicator
10. Left Volume Control
11. Right Limit LED indicator
12. Right Volume Control
13. Subwoofer Volume Control
14. Right and left channel input Combo socket
RCA line inputs (R+L)
15. Right and left channel output Combo socket
16. Right and left channel speaker out
17. Main power switch (ON/OFF)
18. Fused LEC mains inlet

Function Description

