

SLSFKEY25

Single-Door Metal Mini Key Safe Box

USER MANUAL

SereneLife

INSTRUCTIONS

To open the key box:

1. Pull the weather cover down to reveal the dials.
2. Rotate dials to the current combination (the combination of the key box is set at factory to **0-0-0-0**).
3. Pull the door fully open and add or remove the keys.
4. Close the door, realign the combination dials to lock the door and conceal your combination.
5. Close the weather cover.



To set your combination:

1. Open the key box (see instruction above)
2. With the key box internal door facing you (the reset button should be on the left side), Push the **RESET** lever on the back of the door to the right and upward (see picture 1).
3. Rotate dials to your desired combination.
 - Ensure they are correctly aligned so that the code is entered accurately (see picture 2).



Picture 1

4. Push the **RESET** lever downward and left, back to the original position. Make sure to check the reset lever is fully back in its original position.

5. Press the latch to make sure it move down smoothly (see picture 1).



Now you have se your password correctly.

6. Close the door, realign the combination dials to lock the door and conceal your combination

7. Close the weather cover.

Important:

1. Keep the weather cover closed to increase weather resistance.
2. We do not recommend using combinations such as 'A-A-A-A' which is easy to crack.
3. It is recommend the dials are rotated weekly to keep them moving freely.

SereneLife



VISIT US ONLINE:

Have a question?

Need service or repair?

Want to leave a comment?

PyleUSA.com/ContactUs

PYLE